

KEY FEATURES

- > Custom-designed
- > Competitive price
- > Extremely Light Weight
- > Solid, high-quality construction



19" LIGHT WEIGHT LCD BUS MONITOR

CUSTOMISED FOR A RANGE OF BUS BRANDS

MultiQ 19" LW BUS LCD monitor is custom-designed for a range of bus brands, e.g. from Scania, Volvo and VDL. This extremely light weight rugged bus monitor is made of structural designed aluminum. The anti-reflective and anti-scratch polycarbonate front glass with

was developed specially for use in busses and trams. This 19" LCD monitor was developed to deliver high quality at an attractive price and with the lowest weight possible and still maintaining a ruggedized design and solution.

19" LIGHT WEIGHT LCD BUS MONITOR

Technical specifications

Panel Type 19" LCD TFT Backlight type LED Resolution 1440 x 900 (16:10) Brightness 300 cd/m² Contrast ratio 1000:1 (typ.) Viewing angle H: 170° Typ. V: 160° Typ. Response time 5 ms Lamp life 30.000 h (min) INPUT SIGNAL Video signal 19" LCD TFT Electrical interface DVI extender via CAT.6 STP Connectors 1440 x 900 POWER Input voltage + 12 V Power consumption 15,1 W (typ.) 20,5 watt (max) DIMENSION Dimension 320 (H) x 463 (W) x 46,2 (D) mm WEIGHT (NET) Weight 4,6 kg ENVIRONMENT Operating temperature		
Backlight type Resolution 1440 x 900 (16:10) Brightness 300 cd/m² Contrast ratio 1000:1 (typ.) Viewing angle H: 170° Typ. V: 160° Typ. Response time 5 ms Lamp life 30.000 h (min) INPUT SIGNAL Video signal 19" LCD TFT Electrical interface DVI extender via CAT.6 STP Connectors 1440 x 900 POWER Input voltage + 12 V Power consumption 15,1 W (typ.) 20,5 watt (max) DIMENSION Dimension 320 (H) x 463 (W) x 46,2 (D) mm WEIGHT (NET) Weight 4,6 kg ENVIRONMENT Operating 0 - 40°C	DISPLAY	
Resolution 1440 x 900 (16:10) Brightness 300 cd/m² Contrast ratio 1000:1 (typ.) Viewing angle H: 170° Typ. V: 160° Typ. Response time 5 ms Lamp life 30.000 h (min) INPUT SIGNAL Video signal 19" LCD TFT Electrical interface DVI extender via CAT.6 STP Connectors 1440 x 900 POWER Input voltage Input voltage + 12 V Power consumption 15,1 W (typ.) 20,5 watt (max) DIMENSION Dimension 320 (H) x 463 (W) x 46,2 (D) mm WEIGHT (NET) Weight 4,6 kg ENVIRONMENT Operating 0 - 40°C	Panel Type	19" LCD TFT
Brightness 300 cd/m² Contrast ratio 1000:1 (typ.) Viewing angle H: 170° Typ. V: 160° Typ. Response time 5 ms Lamp life 30.000 h (min) INPUT SIGNAL Video signal 19" LCD TFT Electrical interface DVI extender via CAT.6 STP Connectors 1440 x 900 POWER Input voltage + 12 V Power consumption 15,1 W (typ.) 20,5 watt (max) DIMENSION Dimension 320 (H) x 463 (W) x 46,2 (D) mm WEIGHT (NET) Weight 4,6 kg ENVIRONMENT Operating 0 - 40°C	Backlight type	LED
Contrast ratio 1000:1 (typ.) Viewing angle H: 170° Typ. V: 160° Typ. Response time 5 ms Lamp life 30.000 h (min) INPUT SIGNAL Video signal 19" LCD TFT Electrical interface DVI extender via CAT.6 STP Connectors 1440 x 900 POWER Input voltage + 12 V Power consumption 15,1 W (typ.) 20,5 watt (max) DIMENSION Dimension 320 (H) x 463 (W) x 46,2 (D) mm WEIGHT (NET) Weight 4,6 kg ENVIRONMENT Operating 0 - 40°C	Resolution	1440 x 900 (16:10)
Viewing angle H: 170° Typ. V: 160° Typ. Response time 5 ms Lamp life 30.000 h (min) INPUT SIGNAL Video signal 19" LCD TFT Electrical interface DVI extender via CAT.6 STP Connectors 1440 x 900 POWER Input voltage + 12 V Power consumption 15,1 W (typ.) 20,5 watt (max) DIMENSION Dimension 320 (H) x 463 (W) x 46,2 (D) mm WEIGHT (NET) Weight 4,6 kg ENVIRONMENT Operating 0 - 40° C	Brightness	300 cd/m ²
V: 160° Typ. Response time 5 ms Lamp life 30.000 h (min) INPUT SIGNAL Video signal 19" LCD TFT Electrical interface DVI extender via CAT.6 STP Connectors 1440 x 900 POWER Input voltage + 12 V Power consumption 15,1 W (typ.) 20,5 watt (max) DIMENSION Dimension 320 (H) x 463 (W) x 46,2 (D) mm WEIGHT (NET) Weight 4,6 kg ENVIRONMENT Operating 0 - 40°C	Contrast ratio	1000:1 (typ.)
Lamp life 30.000 h (min) INPUT SIGNAL Video signal 19" LCD TFT Electrical interface DVI extender via CAT.6 STP Connectors 1440 x 900 POWER Input voltage + 12 V Power consumption 15,1 W (typ.) 20,5 watt (max) DIMENSION Dimension 320 (H) x 463 (W) x 46,2 (D) mm WEIGHT (NET) Weight 4,6 kg ENVIRONMENT Operating 0-40°C	Viewing angle	
INPUT SIGNAL Video signal 19" LCD TFT Electrical interface DVI extender via CAT.6 STP Connectors 1440 x 900 POWER Input voltage + 12 V Power consumption 15,1 W (typ.) 20,5 watt (max) DIMENSION Dimension 320 (H) x 463 (W) x 46,2 (D) mm WEIGHT (NET) Weight 4,6 kg ENVIRONMENT Operating 0 - 40°C	Response time	5 ms
Video signal 19" LCD TFT Electrical interface DVI extender via CAT.6 STP Connectors 1440 x 900 POWER Input voltage + 12 V Power consumption 15,1 W (typ.) 20,5 watt (max) DIMENSION Dimension 320 (H) x 463 (W) x 46,2 (D) mm WEIGHT (NET) Weight 4,6 kg ENVIRONMENT Operating 0 - 40°C	Lamp life	30.000 h (min)
Electrical interface DVI extender via CAT.6 STP Connectors 1440 x 900 POWER Input voltage + 12 V Power consumption 15,1 W (typ.) 20,5 watt (max) DIMENSION Dimension 320 (H) x 463 (W) x 46,2 (D) mm WEIGHT (NET) Weight 4,6 kg ENVIRONMENT Operating 0 - 40°C	INPUT SIGNAL	
Connectors 1440 x 900 POWER Input voltage + 12 V Power consumption 15,1 W (typ.) 20,5 watt (max) DIMENSION Dimension 320 (H) x 463 (W) x 46,2 (D) mm WEIGHT (NET) Weight 4,6 kg ENVIRONMENT Operating 0 - 40°C	Video signal	19" LCD TFT
POWER Input voltage + 12 V Power consumption 15,1 W (typ.) 20,5 watt (max) DIMENSION Dimension 320 (H) x 463 (W) x 46,2 (D) mm WEIGHT (NET) Weight 4,6 kg ENVIRONMENT Operating 0 - 40°C	Electrical interface	DVI extender via CAT.6 STP
Input voltage + 12 V Power consumption 15,1 W (typ.) 20,5 watt (max) DIMENSION Dimension 320 (H) x 463 (W) x 46,2 (D) mm WEIGHT (NET) Weight 4,6 kg ENVIRONMENT Operating 0 - 40°C	Connectors	1440 x 900
Power consumption 15,1 W (typ.) 20,5 watt (max) DIMENSION Dimension 320 (H) x 463 (W) x 46,2 (D) mm WEIGHT (NET) Weight 4,6 kg ENVIRONMENT Operating 0 - 40°C	POWER	
DIMENSION Dimension 320 (H) x 463 (W) x 46,2 (D) mm WEIGHT (NET) Weight 4,6 kg ENVIRONMENT Operating 0 - 40°C	Input voltage	+ 12 V
Dimension 320 (H) x 463 (W) x 46,2 (D) mm WEIGHT (NET) Weight 4,6 kg ENVIRONMENT Operating 0 - 40°C	Power consumption	15,1 W (typ.) 20,5 watt (max)
WEIGHT (NET) Weight 4,6 kg ENVIRONMENT Operating 0 - 40°C	DIMENSION	
Weight 4,6 kg ENVIRONMENT Operating 0 - 40°C	Dimension	320 (H) x 463 (W) x 46,2 (D) mm
ENVIRONMENT Operating	WEIGHT (NET)	
Operating 0 - 40°C	Weight	4,6 kg
. () - 4()-(ENVIRONMENT	
		0 - 40°C

GENERAL	
Included accessories	Bay for MultiQ DVI receiver
Regulations	Safety: CE
Warranty	3 years SendIT
Security	Kensington locking capability.
Approvals	E-mark compliant
OPTIONS	
Protection	3 mm laminated, anti-reflective coated
	acrylic glass
Connectors	VGA, DVI-D
MOUNTING	
Mounting	M4 mounting nuts –
	8 on the backside and 2+2 on the sides.
	Customized mounting brackets can be
	made upon request.

^{*} Specifications are subject to change without notice. For monitors with integrated media player, the warranty is 3 years.



RoHS Comiliant 2002/95/EG

©2013 MultiQ are registered trademarks or trademark applications of MultiQ International AB in various jurisdictions. All other company names and products are trademarks or registered trademarks of their respective companies. We reserve the right to change the specifications without prior notice.