



MultiQ 15"

Trueflat 4:3, Multi-touch

KEY FEATURES

- 10 touch points
- Frameless
- 24/7 operations
- Suits all public environments

MultiQ 15" Trueflat 4:3, Multi-touch

P-LINE

| DISPLAY | |
|-----------------------|--|
| Panel Type | 15", LCD |
| Backlight type | LED (external diver) |
| Active display area | 304,4 (H) x 228,1 (V) mm |
| Resolution | 1024 x 768 |
| Brightness | 450 cd/m ² (Typ.) |
| Contrast ratio | 700:1 (typ.) |
| Viewing angle | 160° (H) x 130° (V) (CR 10:1, Typ.) |
| Number of colors | 16.2 M Colors (RGB 8-bits) |
| Response time | 8 ms (typ on/off) |
| Pixel dimensions | 0,297 (H) x 0,297 (V) |
| OSD Control | Auto Set, Brightness, Contrast, Color, Position, Image, Miscellaneous. |
| Hot keys functions | Control key locking, Quick brightness and contrast adjustment, Auto Set. |
| MTBF/ Lamp life | 50.000 h |
| INPUT SIGNAL | |
| Video signal | VGA: Analog 0,7 Vp-p. 75 ohm. DVI: REV 1.0 (Transition Minimised Differential Signaling) |
| Sync. signal | TTL Level, Positive/Negative, Separate sync (VGA) |
| Connectors | DVI-I, DC-in |
| POWER | |
| AC/DC adapter 50-60Hz | Input: AC 100-240 V, 50-60Hz Output: +12 V DC, 3A |
| Power consumption | 14,5W (est.) Power save mode suspend: ≤ 2W Power save mode off: ≤ 1 W |
| Power management | VESA DPMS Compatible |

| DIMENSIONS | |
|-----------------------|--|
| With VESA | 283 (H) x 356 (W) x 49 (D) mm |
| WEIGHT | |
| With VESA | 5,2 kg |
| ENVIRONMENT | |
| Operating temperature | 0 - 40°C |
| Transport & Storage | Operating Temp: 0 - +40°C Operating humidity: 8- 90% |
| Plug & Play | DCC2B |
| Incl accessories | AC/DC adapter - 1,5 m (black), Power cord - 1,8 m (black), DVI-I cable 1,8 m DVI-D cable 1,8 m DVI-I to VGA QCODS1459Y1D-MA OPTIONS touch: USB cable touch - 1,8 m (black) PowerUSB hub output |
| Regulations | CE, FCC, UL, WEEE, CB, CEL, CCC, RoHS |
| Warranty | 3 years SendIT |
| Security | Table locking (stand), Kensington locking capability. |
| TOUCH | |
| Type | Projective capacitive multi-touch, |
| Driver Support | Android 2.0, 2.1, 2.2, 2.3 and 4.0 Windows 7 (x86/x64) Windows 8 (x86/x64) Linux with kernel 2.6.32 and above, drivers available as is. |
| OTHER | |
| Accessories | Wall bracket kit |
| Speakers | 2 x 1,5 W, Serial or USB input |
| MSR | MagTek 3 tracks, USB, USB-KeyB, Serial |
| Other | Power USB-hub |
| Glass | Anti reflex |

